



SAFETY DATA SHEET

Version #: 01
Issue date: 16-November-2023
Revision date: -
Supersedes date: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture STEEL-IT 5904 High Temp & Corrosion-Resistant Coating

Registration number -

Synonyms None.

Product code FGPA5904P (pint), FGPA5904Q (quart), FGPA5904G (gallon)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint / Industrial coating.
High temperature coating
Category: Pigmented metallic coating.

Uses advised against Uses other than the recommended use.

1.3. Details of the supplier of the safety data sheet

Manufacturer Stainless Steel Coatings, Inc.
Address 835 Sterling Road, Lancaster MA 01523-2915, USA
Telephone +1 (978) 365-9828
E-mail sds@STEEL-IT.com

Supplier HM Industrieservice GmbH
Address Großer Sand 3
76698 Ubstadt-Weiher, Germany
Telephone +49 7251 44127-0
Fax +49 7251 44127-29
E-mail info@hm-industrie.de
Website www.hm-industrie.de

1.4. Emergency telephone number CHEMTREC:
+1-703-527-3887 (International)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Austria National Poisons Information Centre +431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Belgium National Poisons Control Centre 070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Bulgaria National Toxicological Information Centre +359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Croatia Poisons Information Centre +385 1 2348 342 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Cyprus Poison Centre 1401 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Czech Republic National Poisons Information Centre +420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons Control Centre +45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
Finland National Poison Information Centre	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Centre	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Greece Poison Information Centre telephone number	(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	+36-80-201-199 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Iceland Poison Centre	(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Latvia Emergency medical aid	113
Latvia Poison and Drug Information Centre	+371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidēliotina informācija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Netherlands National Poisons Information Centre (NVIC)	NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Centre	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Portugal Poison Centre	800 250 250
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Spain Toxicology Information Service	+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Centre	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Ireland National Poisons Information Centre	353 (1) 809 2566 Healthcare Professionals: 24 hours, 7 days a week

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
---------------------------	------------	--------------------------------

Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
-----------------------------------	------------	---------------------------------------

Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
--------------------	------------	---

Carcinogenicity (inhalation)	Category 2	H351 - Suspected of causing cancer by inhalation.
------------------------------	------------	---

Specific target organ toxicity - single exposure
Specific target organ toxicity - single exposure
Specific target organ toxicity - repeated exposure

Category 3 respiratory tract irritation
Category 3 narcotic effects
Category 2 (central nervous system, kidneys, liver, respiratory tract)

H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs (central nervous system, kidneys, liver, respiratory tract) through prolonged or repeated exposure.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Feldspar, Nickel, Quartz, Xylene

Hazard pictograms



Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer by inhalation.
H373 May cause damage to organs (central nervous system, kidneys, liver, respiratory tract) through prolonged or repeated exposure.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P308 + P313 IF exposed or concerned: Get medical advice/attention.
P370 + P378 In case of fire: Use water fog, foam, dry chemical powder, carbon dioxide to extinguish.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal

Not assigned.

Supplemental information on the label

None.

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.
The mixture does not contain any substances having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Mica	20 - 25	12001-26-2 601-648-2	-	-	
Classification: -					
Xylene	20 - 25	1330-20-7 215-535-7	-	601-022-00-9	#

Classification: Flam. Liq. 3;H226, Acute Tox. 4;H312;(ATE: 1100 mg/kg bw), Acute Tox. 4;H332;(ATE: 11 mg/l), Skin Irrit. 2;H315, Eye Irrit. 2;H319, STOT SE 3;H335;H336, STOT RE 2;H373, Asp. Tox. 1;H304

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Ethylbenzene	5 - 10	100-41-4 202-849-4	-	601-023-00-4	#
Classification: Flam. Liq. 2;H225, Acute Tox. 4;H332;(ATE: 17,4 mg/l), STOT RE 2;H373, Asp. Tox. 1;H304, Aquatic Chronic 3;H412					
Feldspar	1 - 5	68476-25-5 270-666-7	-	-	
Classification: Eye Irrit. 2;H319, STOT SE 3;H335					
Kaolin	1 - 5	1332-58-7 310-194-1	-	-	
Classification: -					
Quartz	1 - 5	14808-60-7 238-878-4	-	-	#
Classification: STOT RE 1;H372					
Chromium	1 - 3	7440-47-3 231-157-5	-	-	#
Classification: -					
Nickel	1 - 3	7440-02-0 231-111-4	-	028-002-01-4	
Classification: Skin Sens. 1;H317, Carc. 2;H351, STOT RE 1;H372					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

Composition comments

The full text for all H-statements is displayed in section 16.

All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Jaundice. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed such as: Carbon oxides. Fumes of metal oxides. Silicon oxide fumes.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours/spray. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Do not breathe mist/vapours/spray. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is immiscible with water and will sediment in water systems. Prevent entry into waterways, sewer, basements or confined areas. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Retain and dispose of contaminated wash water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labelled containers.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment.

Do not breathe mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Persons susceptible to allergic reactions should not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

TRGS 510 storage class: 3.

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tonnes; Upper-tier requirements = 200 tonnes)

7.3. Specific end use(s)

Paint / Industrial coating.
High temperature coating
Category: Pigmented metallic coating.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits**Austria. MAK List Components**

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	MAK	2 mg/m3	
Ethylbenzene (CAS 100-41-4)	Ceiling	880 mg/m3	
		200 ppm	
	MAK	440 mg/m3	
Kaolin (CAS 1332-58-7)		100 ppm	
	MAK	5 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
Mica (CAS 12001-26-2)		10 mg/m3	Respirable fraction.
	MAK	10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fraction.
Quartz (CAS 14808-60-7)	MAK	0,05 mg/m3	Respirable dust.
Xylene (CAS 1330-20-7)	MAK	221 mg/m3	
		50 ppm	
	STEL	442 mg/m3	
		100 ppm	

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m3	
Ethylbenzene (CAS 100-41-4)	STEL	551 mg/m3	
		125 ppm	
	TWA	87 mg/m3	
Kaolin (CAS 1332-58-7)		20 ppm	
	TWA	2 mg/m3	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	3 mg/m3	
Nickel (CAS 7440-02-0)	TWA	1 mg/m3	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	
		100 ppm	
	TWA	221 mg/m3	
		50 ppm	

Bulgaria. OEL values of carcinogens and mutagens at work (Reg. 10/2003 on prot. from carcinogens and mutagens at work, Ann. 1), as amended

Components	Type	Value	Form
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction and dust

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m3	
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
	TWA	435 mg/m3	
Feldspar (CAS 68476-25-5)	TWA	6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	6 mg/m3	Inhalable fraction.

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Type	Value	Form
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable fraction.
		6 mg/m3	Inhalable fraction.
		3 mg/m3	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m3	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	
		100 ppm	
	TWA	221 mg/m3	50 ppm

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	MAC	2 mg/m3	
Ethylbenzene (CAS 100-41-4)	MAC	442 mg/m3	
		100 ppm	
		884 mg/m3	
Kaolin (CAS 1332-58-7)	MAC	200 ppm	
		2 mg/m3	Respirable dust.
Mica (CAS 12001-26-2)	MAC	10 mg/m3	Total dust.
		0,8 mg/m3	Respirable dust.
Nickel (CAS 7440-02-0)	MAC	0,5 mg/m3	
Quartz (CAS 14808-60-7)	MAC	0,1 mg/m3	
Xylene (CAS 1330-20-7)	MAC	221 mg/m3	
		50 ppm	
	STEL	442 mg/m3	100 ppm

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended

Components	Type	Value
Nickel (CAS 7440-02-0)	TWA	1 mg/m3

Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)

Components	Type	Value
Chromium (CAS 7440-47-3)	TWA	2 mg/m3
		884 mg/m3
		200 ppm
Ethylbenzene (CAS 100-41-4)	STEL	442 mg/m3
		100 ppm
		442 mg/m3
Xylene (CAS 1330-20-7)	STEL	100 ppm
		442 mg/m3
	TWA	221 mg/m3
		50 ppm

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	Ceiling	1,5 mg/m3	Aerosol, inhalable.
	TWA	0,5 mg/m3	Dust.
		0,5 mg/m3	Aerosol, inhalable.
Ethylbenzene (CAS 100-41-4)	Ceiling	500 mg/m3	

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Components	Type	Value	Form
	TWA	200 mg/m ³	
Iron (Massive metal) (CAS 7439-89-6)	TWA	10 mg/m ³	
Mica (CAS 12001-26-2)	TWA	2 mg/m ³	Respirable dust.
		10 mg/m ³	Total dust.
Nickel (CAS 7440-02-0)	Ceiling	1 mg/m ³	Aerosol, inhalable.
	TWA	0,5 mg/m ³	Aerosol, inhalable.
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable dust.
Xylene (CAS 1330-20-7)	Ceiling	400 mg/m ³	
	TWA	200 mg/m ³	

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TLV	0,5 mg/m ³	Dust.
Ethylbenzene (CAS 100-41-4)	TLV	217 mg/m ³	
		50 ppm	
Kaolin (CAS 1332-58-7)	TLV	2 mg/m ³	Respirable.
Nickel (CAS 7440-02-0)	TLV	0,05 mg/m ³	Dust.
Quartz (CAS 14808-60-7)	TLV	0,3 mg/m ³	Total
		0,1 mg/m ³	Respirable.
Xylene (CAS 1330-20-7)	TLV	109 mg/m ³	
		25 ppm	

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³	
		200 ppm	
	TWA	442 mg/m ³	
		100 ppm	
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Fine dust, respiratory fraction
Xylene (CAS 1330-20-7)	STEL	450 mg/m ³	
		100 ppm	
	TWA	200 mg/m ³	
		50 ppm	

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	880 mg/m ³	
		200 ppm	
	TWA	220 mg/m ³	
		50 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable.
Mica (CAS 12001-26-2)	TWA	10 mg/m ³	Dust.
Nickel (CAS 7440-02-0)	TWA	0,01 mg/m ³	Respirable.
Quartz (CAS 14808-60-7)	TWA	0,05 mg/m ³	Respirable.
Xylene (CAS 1330-20-7)	STEL	440 mg/m ³	

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health

Components	Type	Value	Form
		100 ppm	
	TWA	220 mg/m3	
		50 ppm	

France. OELs. Indicative Occupational Exposure Limits as Prescribed by Order of 30 June 2004, as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	VME	2 mg/m3	

France. OELs. Occupational Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	VLE	442 mg/m3	
		100 ppm	
	VME	88,4 mg/m3	
		20 ppm	
Quartz (CAS 14808-60-7)	VME	0,1 mg/m3	Respirable dust.
Xylene (CAS 1330-20-7)	VLE	442 mg/m3	
		100 ppm	
	VME	221 mg/m3	
		50 ppm	

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	VLE	442 mg/m3	
Regulatory status:	Regulatory binding (VRC)		
		100 ppm	
Regulatory status:	Regulatory binding (VRC)		
	VME	88,4 mg/m3	
Regulatory status:	Regulatory binding (VRC)		
		20 ppm	
Regulatory status:	Regulatory binding (VRC)		
Kaolin (CAS 1332-58-7)	VME	4 mg/m3	Total dust.
Regulatory status:	Regulatory binding (VRC)		
		10 mg/m3	
Regulatory status:	Indicative limit (VL)		
		0,9 mg/m3	Respirable dust.
Regulatory status:	Regulatory binding (VRC)		
Mica (CAS 12001-26-2)	VME	4 mg/m3	Total dust.
Regulatory status:	Regulatory binding (VRC)		
		0,9 mg/m3	Respirable dust.
Regulatory status:	Regulatory binding (VRC)		
Nickel (CAS 7440-02-0)	VME	1 mg/m3	
Regulatory status:	Indicative limit (VL)		
Quartz (CAS 14808-60-7)	VME	0,1 mg/m3	Respirable fraction.
Regulatory status:	Regulatory binding (VRC)		
Xylene (CAS 1330-20-7)	VLE	442 mg/m3	
Regulatory status:	Regulatory binding (VRC)		
		100 ppm	
Regulatory status:	Regulatory binding (VRC)		
	VME	221 mg/m3	
Regulatory status:	Regulatory binding (VRC)		
		50 ppm	
Regulatory status:	Regulatory binding (VRC)		

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	88 mg/m3	
		20 ppm	
Kaolin (CAS 1332-58-7)	TWA	4 mg/m3	Inhalable dust.
Mica (CAS 12001-26-2)	TWA	4 mg/m3	Inhalable dust.
Xylene (CAS 1330-20-7)	TWA	220 mg/m3	
		50 ppm	

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	AGW	2 mg/m3	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	AGW	88 mg/m3	
		20 ppm	
Kaolin (CAS 1332-58-7)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Mica (CAS 12001-26-2)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Nickel (CAS 7440-02-0)	AGW	0,03 mg/m3	Inhalable fraction.
		0,006 mg/m3	Respirable fraction.
Xylene (CAS 1330-20-7)	AGW	200 mg/m3	

Greece. OELs, Presidential Decree No. 307/1986, as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	1 mg/m3	
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
		435 mg/m3	
Xylene (CAS 1330-20-7)	STEL	100 ppm	
		650 mg/m3	
		150 ppm	
	TWA	435 mg/m3	
		100 ppm	

Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m3	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		442 mg/m3	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable dust.
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	
		221 mg/m3	

Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m3	Dust.
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
		200 mg/m3	
	TWA	50 ppm	
		2 mg/m3	Respirable dust.

Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended

Components	Type	Value	Form
Mica (CAS 12001-26-2)	TWA	5 mg/m ³	Respirable dust.
		10 mg/m ³	Total dust.
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m ³	Dust.
Quartz (CAS 14808-60-7)	TWA	0,3 mg/m ³	Total dust.
		0,1 mg/m ³	Respirable dust.
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
		100 ppm	
	TWA	109 mg/m ³	
		25 ppm	

Ireland. OELVs, Schedules 1 & 2, Code of Practise for Chemical Agents and Carcinogens Regulations

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³	
		200 ppm	
	TWA	442 mg/m ³	
		100 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable dust.
Mica (CAS 12001-26-2)	TWA	3 mg/m ³	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable dust.
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
		100 ppm	
	TWA	221 mg/m ³	
		50 ppm	

Italy. OELs

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³	
		200 ppm	
	TWA	442 mg/m ³	
		100 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	0,1 mg/m ³	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	1,5 mg/m ³	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0,025 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
		100 ppm	
	TWA	221 mg/m ³	
		50 ppm	

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³	
		200 ppm	
	TWA	442 mg/m ³	
		100 ppm	

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended

Components	Type	Value	Form
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable dust.
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
		100 ppm	
	TWA	221 mg/m ³	
		50 ppm	

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements (Hygiene Norm HN 23:2007)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³	
		200 ppm	
	TWA	442 mg/m ³	
		100 ppm	
Kaolin (CAS 1332-58-7)	TWA	5 mg/m ³	Respirable fraction.
		10 mg/m ³	Inhalable fraction.
Mica (CAS 12001-26-2)	TWA	5 mg/m ³	Respirable fraction.
		10 mg/m ³	Inhalable fraction.
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
		100 ppm	
	TWA	221 mg/m ³	
		50 ppm	

Luxembourg. Chemical Substances Prohibited at Work (Annex III), G.D.R. of 14 November 2016, OJ Memorial A, n ° 235/2016, as amended

Components	Type	Value	Form
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable dust.

Luxembourg. OELs. Binding Occupational Exposure Limit Values (Annex I), G.D.R. of 14 November 2016, OJ Memorial A, n ° 235/2016, as amended

Components	Type	Value
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³
		200 ppm
	TWA	442 mg/m ³
		100 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³
		100 ppm
	TWA	221 mg/m ³
		50 ppm

Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended

Components	Type	Value
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³
		200 ppm
	TWA	442 mg/m ³
		100 ppm

Malta. OELs. Protection of Health and Safety of Workers from Risks related to Chemical Agents at Work (L.N 227/2003 Schedules I and V), as amended

Components	Type	Value
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³ 100 ppm
	TWA	221 mg/m ³ 50 ppm

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Government Gazette no. 252, 29 December 2006), as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	430 mg/m ³	
	TWA	215 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,075 mg/m ³	Respirable dust.
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
	TWA	210 mg/m ³	

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	TLV	20 mg/m ³	
		5 ppm	
Nickel (CAS 7440-02-0)	TLV	0,05 mg/m ³	
Quartz (CAS 14808-60-7)	TLV	0,3 mg/m ³	Total dust.
		0,05 mg/m ³	Respirable dust.
Xylene (CAS 1330-20-7)	TLV	108 mg/m ³	
		25 ppm	

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	400 mg/m ³	
	TWA	200 mg/m ³	
Kaolin (CAS 1332-58-7)	TWA	10 mg/m ³	Inhalable fraction.
Nickel (CAS 7440-02-0)	TWA	0,25 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	STEL	200 mg/m ³	
	TWA	100 mg/m ³	

Portugal. Decree-Law No. 24/2012, Occupational Exposure Limit Values, Annex II, as amended

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³
		200 ppm
	TWA	442 mg/m ³ 100 ppm
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³ 100 ppm
		TWA

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m3	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	1,5 mg/m3	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0,025 mg/m3	Respirable fraction.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m3	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
	TWA	442 mg/m3	
		100 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable fraction.
Nickel (CAS 7440-02-0)	STEL	0,5 mg/m3	
	TWA	0,1 mg/m3	
Xylene (CAS 1330-20-7)	STEL	442 mg/m3	
		100 ppm	
	TWA	221 mg/m3	
		50 ppm	

Slovakia. OELs for carcinogens and mutagens. Regulation No. 356/2006 on carcinogenic and mutagenic substances, as amended

Components	Type	Value	Form
Nickel (CAS 7440-02-0)	TWA	0,05 mg/m3	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m3	Respirable fraction.

Slovakia. OELs. Decree of the government of the Slovak Republic concerning protection of health in work with chemical agents

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m3	
Ethylbenzene (CAS 100-41-4)	TWA	442 mg/m3	
		100 ppm	
Iron (Massive metal) (CAS 7439-89-6)	TWA	6 mg/m3	
Kaolin (CAS 1332-58-7)	TWA	10 mg/m3	Dust.
Mica (CAS 12001-26-2)	TWA	2 mg/m3	Respirable fraction.
		10 mg/m3	Total
Xylene (CAS 1330-20-7)	TWA	221 mg/m3	
		50 ppm	

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3	
		200 ppm	
Mica (CAS 12001-26-2)	TWA	2 mg/m3	Respirable fraction.

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Type	Value	Form
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
		100 ppm	

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Ann. I 100/2001), as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	KTV	2 mg/m ³	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	KTV	884 mg/m ³	
		200 ppm	
Kaolin (CAS 1332-58-7)	KTV	20 mg/m ³	Inhalable fraction.
		2,5 mg/m ³	Respirable fraction.
Mica (CAS 12001-26-2)	KTV	20 mg/m ³	Inhalable fraction.
		2,5 mg/m ³	Respirable fraction.
Nickel (CAS 7440-02-0)	KTV	0,048 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	KTV	442 mg/m ³	
		100 ppm	

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	TWA	442 mg/m ³	
		100 ppm	
Kaolin (CAS 1332-58-7)	TWA	10 mg/m ³	Inhalable fraction.
		1,25 mg/m ³	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	10 mg/m ³	Inhalable fraction.
		1,25 mg/m ³	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	0,006 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	TWA	221 mg/m ³	
		50 ppm	

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³	
		200 ppm	
		441 mg/m ³	
Kaolin (CAS 1332-58-7)	TWA	100 ppm	
		2 mg/m ³	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	3 mg/m ³	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	1 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,05 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	STEL	442 mg/m ³	
		100 ppm	
		221 mg/m ³	
	TWA	50 ppm	

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m ³	Total dust.

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Type	Value	Form
Ethylbenzene (CAS 100-41-4)	Ceiling	884 mg/m ³	
		200 ppm	
	TWA	220 mg/m ³ 50 ppm	
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m ³	Total dust.
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable dust.
Xylene (CAS 1330-20-7)	Ceiling	442 mg/m ³	
		100 ppm	
	TWA	221 mg/m ³ 50 ppm	

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m ³	Inhalable fraction.
Ethylbenzene (CAS 100-41-4)	STEL	220 mg/m ³	
		50 ppm	
	TWA	220 mg/m ³ 50 ppm	
Kaolin (CAS 1332-58-7)	TWA	3 mg/m ³	Respirable fraction.
Mica (CAS 12001-26-2)	TWA	3 mg/m ³	Respirable fraction.
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m ³	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0,15 mg/m ³	Respirable fraction.
Xylene (CAS 1330-20-7)	STEL	440 mg/m ³	
		100 ppm	
	TWA	220 mg/m ³ 50 ppm	

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0,5 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	552 mg/m ³	
		125 ppm	
	TWA	441 mg/m ³ 100 ppm	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable dust.
Mica (CAS 12001-26-2)	TWA	10 mg/m ³	Inhalable
		0,8 mg/m ³	Respirable.
	TWA	0,5 mg/m ³	
Nickel (CAS 7440-02-0)	TWA	0,5 mg/m ³	
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable.
Xylene (CAS 1330-20-7)	STEL	441 mg/m ³	
		100 ppm	
	TWA	220 mg/m ³ 50 ppm	

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	2 mg/m ³	
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m ³	

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
Xylene (CAS 1330-20-7)	TWA	200 ppm
		442 mg/m ³
	STEL	100 ppm
		442 mg/m ³
		100 ppm
		221 mg/m ³
TWA	50 ppm	

Components	Type	Value	Form
Quartz (CAS 14808-60-7)	TWA	0,1 mg/m ³	Respirable fraction and dust

Biological limit values

Croatia. BELs (BGV). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and BELs, Annex IV (NN 91/2018), as amended

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	1,5 g/g	Mandelic acid	Creatinine in urine	*
	1,5 mg/l	ethylbenzene	Blood	*
	1,12 mol/mol	Mandelic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	14,1 umol/l	ethylbenzene	Blood	*
	1,5 g/g	Methylhippuric acids	Creatinine in urine	*
	1,5 mg/l	xylene	Blood	*
	0,88 mol/mol	Methylhippuric acids	Creatinine in urine	*
	14,13 umol/l	xylene	Blood	*

* - For sampling details, please see the source document.

Czech Republic. BELs. Government Decree 432/2003 Sb., as amended

Components	Value	Determinant	Specimen	Sampling Time
Chromium (CAS 7440-47-3)	0,065 µmol/mmol	Total chromium	Creatinine in urine	*
	0,03 mg/g	Total chromium	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	1100 µmol/mmol	Mandelic acid	Creatinine in urine	*
	1500 mg/g	Mandelic acid	Creatinine in urine	*
Nickel (CAS 7440-02-0)	0,077 µmol/mmol	Nickel	Creatinine in urine	*
	0,04 mg/g	Nickel	Creatinine in urine	*
Xylene (CAS 1330-20-7)	820 µmol/mmol	Methylhippuric acids	Creatinine in urine	*
	1400 mg/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, Social Affairs and Ministry of Health

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	5,2 mmol/l	Mandelic acid	Urine	*
Nickel (CAS 7440-02-0)	0,1 umol/l	Nickel	Urine	*
Xylene (CAS 1330-20-7)	5 mmol/l	Methylhippuric acids	Urine	*

* - For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS), ND 2065)

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	1500 mg/g	Acide mandélique	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1500 mg/g	Acides méthylhippuriques	Creatinine in urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	250 mg/g	Mandelsäure plus Phenylglyoxyssäure	Creatinine in urine	*
Xylene (CAS 1330-20-7)	2000 mg/l	Methylhippur-(Tolur-) säure (alle Isomere)	Urine	*

* - For sampling details, please see the source document.

Hungary. BELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 3&4, as amended

Components	Value	Determinant	Specimen	Sampling Time
Chromium (CAS 7440-47-3)	0,022 µmol/mmol	chromium	Creatinine in urine	*
	0,01 mg/g	chromium	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	1110 µmol/mmol	mandelic acid	Creatinine in urine	*
	1500 mg/g	mandelic acid	Creatinine in urine	*
Nickel (CAS 7440-02-0)	0,051 µmol/l	Nickel	Urine	*
	0,003 mg/l	Nickel	Urine	*
Xylene (CAS 1330-20-7)	860 µmol/mmol	methyl hippuric acids	Creatinine in urine	*
	1500 mg/g	methyl hippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	8,03 mg/g	2 and 4-ethylphenol	Creatinine in urine	*
	12 mg/l	2 and 4-ethylphenol	Urine	*
Xylene (CAS 1330-20-7)	1334 mg/g	Methylhippuric acids	Creatinine in urine	*
	2000 mg/l	Methylhippuric acids	Urine	*
	1,5 mg/l	xylene	Blood	*

* - For sampling details, please see the source document.

Spain. BELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 3-Valores Límite Biológicos (VLB)

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	700 mg/g	Suma del ácido mandélico y el ácido fenilglioxílico	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1 g/g	Ácidos metilhipúricos	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle BAT-Werte

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	600 mg/g	Mandelsäure + Phenylglyoxylsäure	Creatinine in urine	*
Nickel (CAS 7440-02-0)	45 µg/l	Nickel	Urine	*
Xylene (CAS 1330-20-7)	2 g/l	Methylhippursäure	Urine	*

* - For sampling details, please see the source document.

UK. BELs. Biological Monitoring Guidance Values (BMGVs) (EH40/2005 (Fourth Edition 2020)), Table 2

Components	Value	Determinant	Specimen	Sampling Time
Chromium (CAS 7440-47-3)	10 µmol/mol	Chromium	Creatinine in urine	*
Xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines**Austria. MAK List**

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Belgium OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Bulgaria OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Croatia ELVs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Czech Republic PELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Denmark GV: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Estonia OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

EU Exposure Limit Values: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Finland Exposure Limit Values: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

France INRS: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

France Mandatory OELs (VLEP): Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Germany DFG MAK (advisory): Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Germany TRGS 900 Limit Values: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.
Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Greece OEL: Skin designation

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Hungary OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Iceland OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Ireland Exposure Limit Values: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Italy OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Danger of cutaneous absorption

Xylene (CAS 1330-20-7) Danger of cutaneous absorption

Latvia OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Lithuania OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Luxembourg OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Malta OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Netherlands OELs (binding): Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Norway Exposure Limit Values: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Portugal OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Romania OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Slovakia OELs for Carcinogens and Mutagens: Skin designation

Nickel (CAS 7440-02-0) Can be absorbed through the skin.

Slovakia OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Spain OELs: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Sweden Threshold Limit Values: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

Switzerland SUVA Limit Values at the Workplace: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

UK EH40 WEL: Skin designation

Ethylbenzene (CAS 100-41-4) Can be absorbed through the skin.

Nickel (CAS 7440-02-0) Can be absorbed through the skin.

Xylene (CAS 1330-20-7) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Provide easy access to water supply and eye wash facilities.
Individual protection measures, such as personal protective equipment	
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	When working with liquids wear splash-proof chemical goggles and face shield unless full facepiece respiratory protection is worn. Eye protection should meet standard EN 166.
Skin protection	
- Hand protection	Wear suitable gloves tested to EN374. Glove material: Nitrile. Use gloves with breakthrough time of 171 +/- 3 minutes. Minimum glove thickness 0.381 (15 mil) mm. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.
- Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with particulate filter (ABEK2/P3). Respiratory protection should meet standard EN 14387. Check with respiratory protective equipment suppliers.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Grey.
Odour	Characteristic of solvents.
Odour threshold	Property has not been measured.
Melting point/freezing point	Technically not possible to determine.
Boiling point or initial boiling point and boiling range	137 - 140 °C (278,6 - 284 °F)
Flammability	Flammable liquid and vapour.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1 % (Xylene)
Explosive limit – upper (%)	7 % (Xylene)
Flash point	26,11 °C (79 °F)
Auto-ignition temperature	464 °C (867,2 °F)
Decomposition temperature	402,4 °C (756,4 °F)
pH	Not applicable (material is insoluble in water).
Kinematic viscosity	2500 mm ² /s (25 °C (77 °F))
Solubility	
Solubility (water)	(< 0,1%) Insoluble in water.
Partition coefficient (n-octanol/water) (log value)	Not applicable, product is a mixture.
Vapour pressure	7,9 mmHg (Xylene) (20 °C (68 °F))
Density and/or relative density	
Density	1,323 g/cm ³ (25 °C (77 °F))
Relative density	1,323 (Water=1) (25 °C (77 °F))

Vapour density	> 1 (Air=1) (25 °C (77 °F))
Particle characteristics	
Particle size	Does not contain nanomaterials.
9.2. Other information	
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.
9.2.2. Other safety characteristics	
Evaporation rate	Property has not been measured.
Flammability	Flammable liquid and vapour.
Viscosity	Property has not been measured.
VOC	295,2 g/l (US VOC) 295,2 g/l (EU VOC) 2,46 lb/gal (US VOC) 2,46 lb/gal (EU VOC)
Other safety characteristics	Total weight solids: 77.66 % w/w (Calculated) Total volume solids: 69.34 % v/v (Calculated)

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Protect against direct sunlight. Contact with incompatible materials.
10.5. Incompatible materials	Strong acids. Strong oxidising agents. Halogens.
10.6. Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Fumes of metal oxides. Silicon oxide fumes.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Suspected of causing cancer by inhalation. May cause irritation to the respiratory system.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms May cause drowsiness or dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Jaundice. Prolonged exposure may cause chronic effects.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
Acute		
Dermal		
LD50	Rabbit	15400 mg/kg
Inhalation		
LC50	Rat	17,4 mg/l, 4 hours
Oral		
LD50	Rat	3500 - 4700 mg/kg
Kaolin (CAS 1332-58-7)		
Acute		
Dermal		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Inhalation		
LC50	Rat	> 2 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Xylene (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	3523 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	May cause an allergic skin reaction.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Suspected of causing cancer by inhalation.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Chromium (CAS 7440-47-3)	3 Not classifiable as to carcinogenicity to humans.	
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans.	
Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.	
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)		
Nickel (CAS 7440-02-0)	Carcinogenic, Category 2.	
Reproductive toxicity	Based on available data, the classification criteria are not met. However: Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.	
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (central nervous system, kidneys, liver, respiratory tract) through prolonged or repeated exposure.	
Aspiration hazard	Based on available data, the classification criteria are not met.	
Mixture versus substance information	No information available.	
11.2. Information on other hazards		
Endocrine disrupting properties	This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.	
Other information	Symptoms may be delayed.	

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life.

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)
<i>Chronic</i>		
Crustacea	EC50	Ceriodaphnia dubia
Kaolin (CAS 1332-58-7)		
Aquatic		
<i>Acute</i>		
Crustacea	LC50	Daphnia magna

Components	Species	Test Results
Nickel (CAS 7440-02-0)		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna) 1 mg/l, 48 hours
	LC50	Calanoid copepod (Eurytemora affinis) >= 7,35 - <= 12,12 mg/l, 96 hours

Xylene (CAS 1330-20-7)

Aquatic

Fish

LC50

Rainbow trout, donaldson trout (Oncorhynchus mykiss)

2,6 mg/l, 96 hours

12.2. Persistence and degradability

No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Partition coefficient

Not applicable, product is a mixture.

n-octanol/water (log Kow)

STEEL-IT 5904 High Temp & Corrosion-Resistant Coating	< 1
Ethylbenzene (CAS 100-41-4)	3,15

Bioconcentration factor (BCF)

Not available.

12.4. Mobility in soil

The product is insoluble in water. Not expected to be mobile in soil.

12.5. Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6. Endocrine disrupting properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

12.7. Other adverse effects

The product contains volatile organic compounds which have a photochemical ozone creation potential.

12.8. Additional information

Estonia Dangerous substances in soil Data

Chromium (CAS 7440-47-3)	Chromium (Cr) 100 mg/kg Chromium (Cr) 300 mg/kg Chromium (Cr) 800 mg/kg
Ethylbenzene (CAS 100-41-4)	ETHYLBENZENE 0,1 mg/kg ETHYLBENZENE 5 mg/kg ETHYLBENZENE 50 mg/kg
Nickel (CAS 7440-02-0)	Nickel (Ni) 150 mg/kg Nickel (Ni) 50 mg/kg Nickel (Ni) 500 mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

EU waste code

The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
08 01 11*

Disposal methods/information

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions

Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1263

14.2. UN proper shipping name Paint

14.3. Transport hazard class(es)

Class 3

Subsidiary risk -

Label(s) 3
Hazard No. (ADR) 30
Tunnel restriction code D/E
14.4. Packing group III
14.5. Environmental hazards No
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number UN1263
14.2. UN proper shipping name Paint
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
14.4. Packing group III
14.5. Environmental hazards No
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number UN1263
14.2. UN proper shipping name Paint
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
14.4. Packing group III
14.5. Environmental hazards No
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number UN1263
14.2. UN proper shipping name Paint
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
14.4. Packing group III
14.5. Environmental hazards No
ERG Code 3L
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

14.1. UN number UN1263
14.2. UN proper shipping name PAINT
14.3. Transport hazard class(es)
Class 3
Subsidiary risk -
14.4. Packing group III
14.5. Environmental hazards
Marine pollutant No
EmS F-E, S-E
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not established.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Chromium (CAS 7440-47-3)

Nickel (CAS 7440-02-0)

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended
- Conditions of restriction given for the associated entry number should be considered

Xylene (CAS 1330-20-7)

75

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Quartz (CAS 14808-60-7)

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended

Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances
Hazard categories in accordance with Regulation (EC) No 1272/2008
- P5a, b or c FLAMMABLE LIQUIDS

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

Contains a substance which is included on the TRGS 907 list of registry of sensitizing substances

Nickel (CAS 7440-02-0)

Nickelverbindungen, Wasserlösliche insbesondere Ni-sulfat und Ni-dichlorid

France regulations

France INRS Table of Occupational Diseases

Quartz (CAS 14808-60-7)

Affections consécutives à l'inhalation de poussières minérales renfermant de la silice cristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille
25

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
EC50: Effective Concentration 50%.
IATA: International Air Transport Association.
IMDG Code: International Maritime Dangerous Goods Code.
IMO: International Maritime Organization.
KTV: Short term exposure limit.
LC50: Lethal Concentration 50%.
LD50: Lethal Dose 50%.
MAC: Maximum Allowed Concentration.
PBT: Persistent, bioaccumulative, toxic.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short-Term Exposure Limit.
TLV: Threshold Limit Value.
TWA : Time Weighed Average Value.
VLE: Exposure Limit Value.
VME: Exposure Average Value.
vPvB: very Persistent, very Bioaccumulative.

References

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
ECHA: European Chemical Agency.
EPA: AQUIRE database
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
NLM: Hazardous Substances Data Base

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H372 Causes damage to organs through prolonged or repeated exposure by inhalation.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer

Stainless Steel Coatings, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.